

**LONG-LASTING COOLING FOR
UNINTERRUPTED SLEEP.**



Presenting

AIKIDO AIR COOLERS

FOR LONG-LASTING COOLING



Higher tank
capacity enabling
uninterrupted sleep

Thicker pads
for enhanced
cooling



LONG-LASTING COOLING FOR UNINTERRUPTED SLEEP.

Beat the heat with the new range of Aikido Air Coolers from V-Guard. Equipped with a higher tank capacity, the Aikido doesn't need frequent refills. It also features thicker cooling pads that ensures it delivers long-lasting cooling. Working in tandem with each other, all of these features give you and your family many nights of uninterrupted sleep. So that every day, everybody can wake up refreshed, think fresh and have a great day.

AIKIDO AIR COOLER FEATURES		
 SUPERIOR PERFORMANCE	 BEST-IN-CLASS AIR DELIVERY	 AN AERODYNAMICALLY BALANCED BODY FOR BETTER STABILITY
 TETRA AIRFLOW COOLING FOR EFFICIENT AIR CIRCULATION	 UNIDRIP FLOW WATER DISTRIBUTION	 LONG-LASTING COOLING MEDIA WITH NANO PORES
 FULLY CLOSABLE HORIZONTAL LOUVERS	 CORROSION RESISTANT FAN BLADES/BLOWER	 WIDE VOLTAGE WORKING RANGE TO TACKLE HIGH/LOW VOLTAGE (160V ~ 270V)
 ENHANCED PROTECTION FOR MAIN MOTOR & PUMP	 CORD WINDING PROVISION	 WORKS ON INVERTERS

* 2 year warranty on motor & pump





DESERT COOLERS



Aikido F85

- Tank capacity: 85 Liter
- Air delivery: 4700 m³/hr
- Air throw distance: 15.2 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision
- Strong 5 No's Caster Wheels



Aikido F70

- Tank capacity: 70 Liter
- Air delivery: 4700 m³/hr
- Air throw distance: 15.2 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision
- Strong 4 No's Caster Wheels

ROOM COOLERS



Aikido F50T

- Tank capacity : 50 Liter
- Air Delivery: 3500 m³/hr
- Air Throw Distance: 12 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision
- With trolley



Aikido F30T

- Tank capacity : 30 Liter
- Air Delivery: 2900 m³/hr
- Air Throw Distance: 10.7 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision
- With trolley

PERSONAL COOLER



Aikido B25

- Tank capacity : 25 Liter
- Air Delivery: 1100 m³/hr
- Air Throw Distance: 7.6 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision
- Strong 4 No's Caster Wheels



Aikido F50

- Tank capacity : 50 Liter
- Air Delivery: 3500 m³/hr
- Air Throw Distance: 12 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision



Aikido F30

- Tank capacity : 30 Liter
- Air Delivery: 2900 m³/hr
- Air Throw Distance: 10.7 meter
- Antifungal Cellulose Honeycomb Cooling Pads
- Easily Openable cooling pads
- Cord winding provision





	TECHNICAL SPECIFICATION							
	Air cooler category	Desert	Desert	Room	Room	Room	Room	Personal
	Technical Specification	Aikido F85	Aikido F70	Aikido F50T	Aikido F30T	Aikido F50	Aikido F30	Aikido B25
Features	Water Tank Capacity up to brim (liter)	85	70	50	30	50	30	25
	Air Device	Corrosion Resistant Plastic Fan Blade	Corrosion Resistant Plastic Fan Blade	Corrosion Resistant Plastic Fan Blade	Corrosion Resistant Plastic Fan Blade	Corrosion Resistant Plastic Fan Blade	Corrosion Resistant Plastic Fan Blade	Corrosion Resistant Plastic Blower
	Water Inlet Provision	Water Inlet Door	Water Inlet Door	Water Inlet Spout	Water Inlet Spout	Water Inlet Spout	Water Inlet Spout	Water Inlet Door
	Water Level Indicator	Provided (Tank Inbuilt)	Provided (Tank Inbuilt)	Provided (Tank Inbuilt)	Provided (Tank Inbuilt)	Provided (Tank Inbuilt)	Provided (Tank Inbuilt)	Provided (Tank Inbuilt)
	Over Flow Hole	Provided	Provided	Provided	Provided	Provided	Provided	Provided
	Openable Cooling Pads	Only Back Panels	Only Back Panels	All Three Panels	All Three Panels	All Three Panels	All Three Panels	Only Back Panel
	Cooling Medium	Cellulose Honeycomb Pad	Cellulose Honeycomb Pad	Cellulose Honeycomb Pad	Cellulose Honeycomb Pad	Cellulose Honeycomb Pad	Cellulose Honeycomb Pad	Cellulose Honeycomb Pad
	Cord Winding provision	Provided	Provided	Provided	Provided	Provided	Provided	Provided
	Handle Provision	Provided	Provided	Provided	Provided	Provided	Provided	Provided
	Portability	5 Nos. Caster Wheel Provided	4 Nos. Caster Wheel Provided	Trolley with 4 Nos. castor wheels provided	Trolley with 4 Nos. castor wheels provided	Without Trolley	Without Trolley	4 Nos. Caster Wheel Provided
	Front & Top Deco panels	Provided	Provided	Provided	Provided	Provided	Provided	Provided
	Power ON LED Indicator	Provided	Provided	Provided	Provided	Provided	Provided	Provided
Performance	Air Throw Distance (approx.) (meter)	15.2	15.2	12	10.7	12	10.7	7.6
	Air Delivery (m ³ /hr)	4700	4700	3500	2900	3500	2900	1100
	Wattage (approx.) [W]	190	190	180	125	180	125	120
Safety	3 Pin Power Cord with Earthing	Provided	Provided	Provided	Provided	Provided	Provided	Provided
	Thermal Overload Protection	Provided	Provided	Provided	Provided	Provided	Provided	Provided
Functions	Air Deflection	4 way	4 way	4 way	4 way	4 way	4 way	4 way
	Speed	3 Speed	3 Speed	3 Speed	3 Speed	3 Speed	3 Speed	3 Speed
	Vertical Louver Movement	Motorized	Motorized	Motorized	Motorized	Motorized	Motorized	Motorized
	Horizontal Louver Movement	Manual	Manual	Manual	Manual	Manual	Manual	Manual
	Fully Closable Horizontal Louvers	Provided	Provided	Provided	Provided	Provided	Provided	Provided
	Works on Inverter	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dimensions	Blower/ Fan Diameter(cm)	40.6	40.6	35.6	35.6	35.6	35.6	20.3
	Product Dimensions (WxDxH) in cm	68 x 52.4 x 110	68 x 52.4 x 104.1	56.5 x 47.0 x 120.2	56.5 x 47.0 x 110.2	56.5 x 47.0 x 80.6	56.5 x 47.0 x 70.6	46 x 37 x 78.1

* All above-mentioned specs are under standard test conditions and actual performance may vary as per usage conditions. Design, Specs and Aesthetics are subject to change without prior notice due to continuous development.

V-Guard Industries Ltd.

Registered Office: 42/962, Vennala High School Road, Vennala, Kochi - 682 028, Kerala.
Ph: 0484-2005000, 4335000 www.vguard.in



V-Guard Care
1800 103 1300 (Toll Free)
1860 180 3000 (Charges Apply)
customercare@vguard.in
CIN: L31200KL1996PLC010010

